


SPECIFICATIONS

Current Rating: 2Amps
Insulator resistance: 5000 Megohms min.
Dielectric Withstanding: AC 500V
Operating Temperature: -40°TO +105°C
Max Processing Temp: 230° TO 260° for 30-60 seconds
Contact Material: Brass
Plating: Gold Flash
Insulator Material: NY-6T

UNSPECIFIED TOLERANCE: ±0.20

Dimensions list



Contacts Per row	Dimensions		Contacts Per row	Dimensions	
	A	B		A	B
1	2.0	0	21	42.0	40.0
2	4.0	2.0	22	44.0	42.0
3	6.0	4.0	23	46.0	44.0
4	8.0	6.0	24	48.0	46.0
5	10.0	8.0	25	50.0	48.0
6	12.0	10.0	26	52.0	50.0
7	14.0	12.0	27	54.0	52.0
8	16.0	14.0	28	56.0	54.0
9	18.0	16.0	29	58.0	56.0
10	20.0	18.0	30	60.0	58.0
11	22.0	20.0	31	62.0	60.0
12	24.0	22.0	32	64.0	62.0
13	26.0	24.0	33	66.0	64.0
14	28.0	26.0	34	68.0	66.0
15	30.0	28.0	35	70.0	68.0
16	32.0	30.0	36	72.0	70.0
17	34.0	32.0	37	74.0	72.0
18	36.0	34.0	38	76.0	74.0
19	38.0	36.0	39	78.0	76.0
20	40.0	38.0	40	80.0	78.0

PCB LAYOUT

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
APPROVALS						
DRAWN			DATE			
ZHIWEI.CHEN			2015.07.07			
CHECKED			TITLE:			
			2.0 单排SMT排针			
APPROVALS			PART NO.			
			GP26-2020WVS-NP			
TOLERANCES ARE			SCALE: 1:1			
30~0.15 10~0.30 5~10			PROJ. 1 OF 1			