



Technical Data
 Material: Brass,machined CuZn38Pb2
 Pin(outer sleeve):Brass,machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated: 2μm /80μm Ni,5μm /200 μSn
 Gold Plated: 2μm /80 μm Ni,0.8 μ gold
 Insulator: PPS UL94V-0

Electrical:
 Current rating: 3Amps/contact max.
 Contact resistance: ≤4mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Operating voltage: 60VAC/DC

Mechanical:
 Operating temperature: -40°C to+105°C
 Soldering temperature: +255°C

APPROVALS		DATE			
DRAWN	ZHIWEI,CHEN	2015.07.07			
CHECKED		TITLE:		2.54MM IC 圓孔插針	
APPROVALS		PART NO.		GP28-0762-2XNP-1196A	
TOLERANCES ARE		30~0.15	±0.30	ANGLE	PROJ.
10~0.30	±0.20	5~0.10	±0.15	±2°	1 OF 1
~ 5	±0.10	DRAWING NO.		SHEET	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.
	A		NEW		