





SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

- 技术参数 SPECIFICATIONS
- ◆ 间距: 2.54 Pitch: 2.54
 - ◆ 极数: 2~20 Poles: 2~20
 - ◆ 适用线规: AWG#28~#22
 - ◆ Applicable Wire: AWG#28~#22
 - ◆ 额定电压: 250V DC,AC(rms)
 - ◆ Rated voltage: 250V DC,AC(rms)
 - ◆ 额定电流: 2.5A AC,DC
 - ◆ Rated Current: 2.5A AC,DC
 - ◆ 耐压值: 1500V AC/minute
 - ◆ Withstand voltage: 1500V AC/min.
 - ◆ 工作温度: -25°C ~ +85°C
 - ◆ Working Temp : -25°C ~ +85°C
 - ◆ 绝缘电阻: ≥1000 MΩ
 - ◆ Insulation resistance: ≥1000 MΩ
 - ◆ 接触电阻: ≤20mΩ
 - ◆ Contact resistance: ≤20mΩ
- 材料 MATERIAL
- ◆ Wafer: 尼龙66 (Nylon66) , UL94-V0
 - ◆ PIN: 黄铜Brass

Circuits	Dimensions (mm)			Circuits	Dimensions (mm)		
	A	B	C		A	B	C
02	2.54	2.54	5.08	12	27.94	27.94	30.48
03	5.08	5.08	7.62	13	30.84	30.84	33.02
04	7.62	7.62	10.16	14	33.02	33.02	35.56
05	10.16	10.16	12.70	15	35.56	35.56	38.10
06	12.70	12.70	15.24	16	38.10	38.10	40.64
07	15.24	15.24	17.78	17	40.64	40.64	43.18
08	17.78	17.78	20.32	18	43.18	43.18	45.72
09	30.32	30.32	22.86	19	45.72	45.72	48.26
10	22.86	22.86	25.40	20	48.26	48.26	50.80
11	25.40	25.40	27.94				

APPROVALS		DATE	GEPU歌普	
DRAWN	ZHIWEI.CHEN	2015.07.07		
CHECKED				
APPROVALS				
TOLERANCES ARE			PART NO.	GP01-2543WR-NP
30~0.15	±0.30	ANGLE	UNIT: mm	SCALE: 1:1
10~30	±0.20			PROJ.
5~10	±0.15	±2°	DRAWING NO.	SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	
	A		NEW	