





Poles	DIM.A	DIM.B
2A	4.25	1.25
3A	5.50	2.50
4A	6.75	3.75
5A	8.00	5.00
6A	9.25	6.25
7A	10.50	7.50
8A	11.75	8.75
9A	13.00	10.00
10A	14.25	11.25
11A	15.50	12.50
12A	16.75	13.75
13A	18.00	15.00
14A	19.25	16.25
15A	20.50	17.50
16A	21.75	18.75



■ 技术参数 SPECIFICATIONS

◆ 适用线规

- ◆ 额定电压: 125V DC/AC(rms)
 - ◆ 额定电流: 1A (AWG #28)
Rated Current: 1A (AWG #28)
 - ◆ 耐压值: 250V AC/minute
Withstand voltage: 250V AC/min.
 - ◆ 工作温度: -40°C ~ +85°C
Working Temp : -40°C ~ +85°C
 - ◆ 绝缘电阻: ≥100 MΩ
Insulation resistance: ≥100 MΩ
 - ◆ 接触电阻: ≤20 mΩ
Contact resistance: ≤20 mΩ
- 材料 MATERIAL
- ◆ 绝缘体: 尼龙46, UL94-V0
Insulator: Nylon46, UL94-V0
 - ◆ 接触针: 磷铜
Contact PIN: Phosphor bronze



P.C.B LAYOUT

				APPROVALS		DATE		GEPU歌普					
				DRAWN		ZHIWEI.CHEN		2015.07.07					
				CHECKED						TITLE:			
				APPROVALS						PART NO. GP01-1250WR-NP			